

Power King Tractor Fluid

Power King Tractor Fluid NT

Power King Tractor Fluid North



Power King Tractor Fluid has been improved. We have now increased the anti-wear and wet brake performance of this oil to beyond the standards of tractor manufacturers branded oils. This fluid is made with no compromises.

Power King Tractor Fluid and Power King Tractor Fluid North are climate customized oils. Use the North version for tractors operated in the northern 25% of the United States and in Canada where it is essential that a fluid provide rapid lubrication at cold winter startup. Use standard version for the rest of the continent.

Both versions of **Power King Tractor Fluid** contain 1% of our NT Oil Additive. For those wanting the ultimate in tractor fluid performance, we offer the **NT** version with 7.5% NT Oil Additive, a 100% synthetic ester. NT Oil Additive helps reduce friction so transmissions and hydraulics will operate cooler. It helps reduce seal and hose deterioration. It resists moisture, preventing nominal amounts of moisture from ever touching the metal inside your machines.

Both fluids are designed for farm and industrial tractors and other uses that require tractor fluid or Hydraulic / Transmission fluid and utilize one fluid to operate power steering units, transmissions, hydraulics and wet brake systems (where brake materials are immersed in fluid).

Power King Tractor Fluid and Power King Tractor Fluid North are colored green to aid identification and prevent misapplication.

Benefits

- Superior Water Tolerance
- Reduced Wet Brake Chatter and Increased Brake Durability
- Will Outperform OEM and Major Branded Oils.
- Meets Requirements of Every Tractor Brand
- Climate Optimized
- High Dispersancy for Clean Operation, particularly in the NT version
- Excellent Seal Compatibility, particularly in the NT version
- A Reasonable Price

Typical Properties

Power King Tractor Fluid

Viscosity @ 100C, cSt	10.0
Viscosity @ 40C, cSt	68.2
Viscosity @ -20C, Brookfield	6.70
Viscosity @ -35C, Brookfield	90,000
Viscosity Index	125
Pour Point, Max	-38C
Flash Point, Min	205C
LVFA, 30 kg load, Friction Test	Pass
SAE Viscosity Grade	10W30

Typical Properties

Power King Tractor Fluid North

Viscosity @ 100C, cSt	8.00
Viscosity @ 40C, cSt	48.0
Viscosity @ -20C, Brookfield	3,500
Viscosity @ -35C, Brookfield	39,500
Viscosity Index	133
Pour Point, max.	-42
Flash Point, min.	200C
LVFA, 30 kg load, Friction Test	Pass
SAE	10W20

Allis Chalmers, Duetz Allis Corporation

Power Fluid 821, Power Fluid 821 XL, 272843, 257541, 246634

Case IH, JI Case, International Harvester Corporation, Dresser Industries

JIC-144, JIC-143/TFD, JIC-145 and MS1210/TCH Fluid, MS-1204 and JIC-185/TFD, MS 1205, MS-1206 (Powerguard PTF), MS-1207 (Hy-Tran Plus), MS-1230 Poclain Equip., B-5, B-6 (Hy-Tran)

Caterpillar

TO-2 (Powershift Transmission)

MTO

Dennison

HF-0 Anti-Wear, HF-1, HF-2

John Deere

JDM J20C/JDM J20D (Hy-Gard), J-14B (303 Fluid), J-14C, J-20A&B, J-21A

Allison

C-2, C-3 & C-4

Ford Motor Co., New Holland Group

ESN-M2C34A & B & C & D, (Hydraulic Oil 134), FNHA-2-C-200, 201, ESN-M2C86-B, ESN-M2C53-A & B, ESN-M2C41, ESN-M2C48-B, M2C134-D

Kubota

UDT Fluid, Universal Transdraulic Fluid

AGCO & Massey Ferguson

M-1141 (Permatran III), M-1135, M-1110, M-1127A & B, M-1129A (Permatran Fluid), (Permatran II)

Renk Bus

Automatic Transmission Fluid

Steiger

Hydraulic Transmission Fluid, SEMS 17001

Versatile

Hydraulic/Gear Fluid, Spec 24M, Spec 23M

Vickers

M-2950-S, I-286-S

Volvo

WB 101/VCE 1273.03

White Farm - New Idea (Also MM & Oliver)

UHTF Q-1705, Q-1802 Type 55, Q-1766, Q-1722 White MP Tractor Oil, Q-1766B Universal HTF, Q-1826 Hydraulic Transmission Fluid (HTF)

Hesston Fiat

Oilofiat Tutela Multi-F, AF-87

Landini

Tractor II Hydraulic Fluid

And the following;

Clark, Link Belt

JCB

Use our 4422 Power King Special Gear Oil Plus NT for JCB

Sundstrand

Power King Tractor Fluid easily passes Sundstrand flow degradation test requirements with fluid and water blend in a Sundstrand Hydrostatic Transmission

Note that fluids named above may be trademarks of their respective suppliers.

Power King Tractor Fluids are available in 330 gallon totes, 55 gallon drums and in 5 gallon pails. They are available by special order in 2.5 gallon jugs.

0-425 and 4-425 SERIES

In Search of *Excellence*

King Oil Lubricants, LLC

Office: 240-707-6464

Fax: 240-328-4444

12314 Huyett Lane

Hagerstown, MD 21740

**OVER 400 SPECIALTY
LUBRICANTS**

